39214-101 Issue 5A

5 - 36V

25mA, UP TO 40°C

-10° TO +60°C

MINIDISC REMOTE INDICATOR PART No. 53832-070/072


THE REMOTE INDICATOR IS POLARITY SENSITIVE

CONNECT POSITIVE LINE TO TERMINAL A OR B

AND NEGATIVE LINE TO TERMINAL C.

MINIDISC REMOTE INDICATOR

PART No. 53832-070/072




DETECTOR RANGE SERIES 60 SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS	CONNECTIONS A & C A & C A & C B & C A & C B & C A & C A & C A & C B & C
VOLTAGE, A & C MAX CURRENT, B & C OPERATING TEMPERATURE	5 - 36V 25mA, UP TO 40°C -10° TO +60°C



MINIDISC REMOTE INDICATOR

PART No. 53832-070/072



DETECTOR RANGE SERIES 60 SERIES 60 INTRINSICALLY SAFE XP95 XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS	CONNECTIONS A & C A & C A & C B & C A & C B & C A & C B & C A & C B & C B & C
VOLTAGE, A & C	5 - 36V
MAX CURRENT, B & C	25mA, UP TO 40°C
OPERATING TEMPERATURE	-10° TO +60°C



MINIDISC REMOTE INDICATOR PART No. 53832-070/072

THE REMOTE INDICATOR IS POLARITY SENSITIVE CONNECT POSITIVE LINE TO TERMINAL A OR B AND NEGATIVE LINE TO TERMINAL C. В

DETECTOR RANGE SERIES 60 SERIES 60 INTRINSICALLY SAFE XP95 XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS	CONNECTIONS A & C A & C A & C A & C A & C A & C B & C B & C B & C B & C C B & C
VOLTAGE, A & C MAX CURRENT, B & C OPERATING TEMPERATURE	5 - 36V 25mA, UP TO 40° -10° TO +60°C



39214-101 Issue 5A


25mA, UP TO 40°C

-10° TO +60°C

CONNECTIONS

5 - 36V

MINIDISC REMOTE INDICATOR PART No. 53832-070/072



DETECTOR RANGE SERIES 60 SERIES 60 INTRINSICALLY SAFE XP95 XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS	CONNECTIONS A & C A & C A & C B & C A & C B & C A & C A & C A & C A & C B & C B & C
VOLTAGE, A & C MAX CURRENT, B & C OPERATING TEMPERATURE	5 - 36V 25mA, UP TO 40°C -10° TO +60°C



39214-101 Issue 5A

MINIDISC REMOTE INDICATOR

PART No. 53832-070/072

THE REMOTE INDICATOR IS POLARITY SENSITIVE CONNECT POSITIVE LINE TO TERMINAL A OR B AND NEGATIVE LINE TO TERMINAL C.

DETECTOR RANGE CONNECTIONS SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY

ALARMSENSE

VOLTAGE, A & C

MAX CURRENT, B & C

OPERATING TEMPERATURE

ORRIS

DETECTOR RANGE

DISCOVERY ALARMSENSE VOLTAGE, A & C


SERIES 60 SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE

MAX CURRENT, B & C

OPERATING TEMPERATURE

MINIDISC REMOTE INDICATOR PART No. 53832-070/072


THE REMOTE INDICATOR IS POLARITY SENSITIVE



DETECTOR RANGE CONNECTIONS SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS VOLTAGE, A & C MAX CURRENT, B & C 25mA, UP TO 40°C OPERATING TEMPERATURE -10° TO +60°C

39214-101 Issue 5A

MINIDISC REMOTE INDICATOR PART No. 53832-070/072



DETECTOR RANGE CONNECTIONS SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS VOLTAGE, A & C 5 - 36V 25mA, UP TO 40°C MAX CURRENT, B & C OPERATING TEMPERATURE -10° TO +60°C