

FE230

Door Holder, Surface Mount, 400N, with Release Button

General

The FE230 is a surface mount door holder, in a Bayblend housing, which offers a 400N holding force and a release button. Cable entry is possible from the back or from the sides, and the release button can be located at the top, or one of the sides.

Magnet construction

The magnet is constructed with a pressed coil and anti-remnance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

For practical ease of installation, the door holder comes complete with electrical screw terminals.

The housing is predrilled in a practical, standard format for rapid mounting.

The door holder is supplied complete with a keeper plate, which offer angular adjustment.

The release button can be position in three different locations: top, left or right

Cable entry can be done in four different locations: back, top, left or right.

Approvals

The FE230 is fully approved according to EN1155.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Keeper plate included

FE230

Door Holder, Surface Mount, 400N, with Release Button

Technical specifications

Electrical

Power supply type	24 VDC
Power consumption	1.6 W
Duty cycle	100%

General

Holding force N (Newton)	400
Release button	Yes
Spark suppression diode	Yes
Reverse polarity protection	Yes

Physical

Physical dimensions	85 x 110 x 38 mm (W x H x D)
---------------------	------------------------------

IP rating

Magnet	IP54
Connection	IP42

EN1155

	Yes
--	-----

