

FE130MS Eco Line magnetic lock 300 Kgf, monitored, surface mount

Description

Eco Line magnetic lock 300 kgs, monitored. Surface mounting.

Application

Medium security applications for internal and external doors. To be mounted inside external doors.

Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle

brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving

parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise

concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



Details

- 300 kgf holding power
- Surface mounted
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Monitored changeover

FE130MS

Eco Line magnetic lock 300 Kgf, monitored, surface mount

Technical specifications

Draduct two	Magnatia
Product type	Magnetic lock
Holding force	
Holding force kgf	300 kgf
(Kilogram force)	
Holding force N (Newtor	n)3000
Monitoring & statu	S
Monitored	Yes
LED indicator	Yes
Door status switch	No
Monitored changeover	Yes
Magnetic bond sensor	Yes
Electrical	
Power supply value	12 / 24 VDC
Current consumption	440 mA (+/- 2,5% @ 13,5 V)
Physical	
Physical dimensions	250 x 47 x 26 mm
Colour	Aluminium
Finish	Vapour blasted aluminium

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

