

## L2 Series Video Surveillance Micro SD (TF) Card

### Introduction

Hikvision L2 series Micro SD (TF) card is specially designed for video surveillance industry. It provides Class 10 R/W speed, adopts TLC NAND with high compatibility and low price, and is mainly applicable to low recording intensity scenes or simple operating scenes like lite storage, standby storage, etc.



### Available Models

HS-TF-L2I/16G,  
HS-TF-L2I/32G,  
HS-TF-L2I/64G,  
HS-TF-L2I/128G

### Features and Functions

- **High Cost Performance**
  - Lower price compared to the cards with the same TLC NAND.
  - Fully satisfies requirements of lite storage.
- **High Compatibility**
  - Optimized by Hikvision storage system, it is compatible with more products than traditional SD (TF) cards.
  - Better performance when used with Hikvision cameras.
- **Ultra-Strong Adaptability**
  - Waterproof, shock proof, X-ray proof, and wide temperature range.



## Specifications

Model	HS-TF-L2I			
Total capacity	16 GB	32 GB	64 GB	128 GB
Available capacity	14.9 GB	30.0 GB	60.0 GB	120.0 GB
Max. read speed	95 MB/s	95 MB/s	95 MB/s	95 MB/s
Max. write speed	20 MB/s	20 MB/s	24 MB/s	24 MB/s
File system	FAT32	FAT32	exFAT	exFAT
Format	MicroSDHC	MicroSDHC	MicroSDXC	MicroSDXC
Speed	Class10, U1	Class10, U1	Class10, U1	Class10, U1
Dimensions	14.99 x 10.92 x 1.02mm (0.59 x 0.43 x 0.04 in)			
NAND flash memory	TLC (Triple-Level Cell)			
Storing temperature	-25 °C to +85°C (-13 °F to +185 °F)			
Operating temperature	0 °C to 70 °C (32 °F to 158 °F)			
Compatibility	Compatible with MicroSDHC, MicroSDXC, MicroSDHC UHS-I and MicroSDXC UHS-I host devices			
Limited warranty period	2 years			

**Note:** Performance test is performed in a specific testing environment. Any change of computer system, operation system, hardware, software, or functions will influence the test result.

Distributed by



**HIKVISION**

**Headquarters**

Rm.01, 21/F, F4 Building,  
5th Phase-NO.1 Software Park,  
Guanshan 1 Rd, East Lake Development Zone,  
Wuhan, China(430040)