

DS-PDPT15AM-LM-WE



- 90°@180° adjustable coverage
- IP65 weather resistance for outdoor application
- Active IR anti-masking
- Multiple enrollment methods and easy installation
- Frequency hopping against jamming for reliable transmission



▪ Specification

Model	DS-PD115AM-LM-WE	
Detection Performance	Detection Method	Passive Infrared,Microwave
	Detection Range	15m
	Detection Angle	90° @ 180° adjustable
	Detection Zones	92
	Detectable Speed	0.3~2m/s
	Sensitivity	Auto,Low
	White Light Filter	10000lux
	Pet Immunity	40Kg
	Microwave Frequency	24GHz(24.15~24.25GHz)
	Digital Temperature Compensation	Support
	Anti-masking	Support
	Adaptable Coverage	Support Pattern mask included
	Feature	Digital Processing
Sealed Optics		Support
Tamper Protection		Front,Rear
Environment Temperature Indicator		Support
Signal Strength Indicator		Support
Anti-Sway Analytics		Support
Interface	Power Switch	Power Up Enrolling
	LED Indicator	Green(Top PIR), Red(Microwave), Orange(Bottom PIR), Green+Orange(Mask), Blue(Alarm)
Transmission	Transmission Technology	Tri-X Wireless
	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	868MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	1.6Km
	Frequency Hopping	Support
	Enrolling Method	Power up,Remote ID,QR Code
Electrical	Standard Battery	5 years in work status


Characteristics	Life	(Standalone: being triggered 20 times per day) (With camera integrated: being triggered and completely uploading captures once per day)
	Power Supply	Battery Powered
	Battery Type	CR123A × 5
	Typical Voltage	3V
General	Operation Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
	Storage Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
	Operation Humidity	10% to 90%
	IP Rate	IP65
	Dimension(WxHxD)	75mm × 202mm × 73mm
	Weight	600g
	Mounting Height	0.8 to 1.2m
	Mounting Method	Wall
	Application Scenario	Outdoor

▪ **Available Model**

DS-PD115AM-LM-WE

▪ **Accessory**

▪ **Optional**



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com