

DS-3E0505HP-E

5-Port Gigabit Unmanaged Hi-PoE Switch

DS-3E0505HP-E switches are layer 2 Hi-PoE switches, providing advanced PoE power supply technology and Gigabit networks design on the basis of high-performance access to ensure stable data upload. The switches support Hi-PoE, long range, port isolation, and PoE watchdog function.



Key Feature

- 3 × gigabit PoE ports, 1 × gigabit Hi-PoE port and 1 × gigabit RJ45 port.
- IEEE 802.3at/af/bt standard for Hi-PoE port (Max. 60 W PoE output).
- IEEE 802.3at/af standard for PoE ports (Max. 30 W PoE output).
- IEEE 802.3, IEEE 802.3u, IEEE 802.3x, and IEEE 802.3ab standard.
- 6 KV surge protection for PoE ports.
- Up to 300 m long-range transmission.
- PoE watchdog to auto detect and restart the cameras that do not respond.
- Port isolation to improve network security.
- Gigabit network access design.
- Wire-speed forwarding.
- Store-and-forward switching.
- Solid high-strength metal shell.
- Reliable fan-free design.




Specification


| Model | | DS-3E0505HP-E |
|--------------------|--------------------------------------|---|
| Network parameters | Port number | 3 × gigabit PoE ports, 1 × gigabit Hi-PoE port and 1 × gigabit RJ45 port |
| | Port type | RJ45 port, full duplex, MDI/MDI-X adaptive |
| | Standard | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, and IEEE 802.3ab |
| | Forwarding mode | Store-and-forward switching |
| | Working mode | Standard mode (default), Extend mode, Isolation mode, PoE watchdog mode |
| | Ports for long-distance transmission | Ports 3 and 4 |
| | MAC address table | 2 K |
| | Switching capacity | 10 Gbps |
| | Packet forwarding rate | 7.44 Mpps |
| | Internal cache | 1 Mbits |
| PoE power supply | PoE standard | Port 1: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt Ports 2 to 4: IEEE 802.3af, IEEE 802.3at |
| | PoE power pin | Ports 1 to 4: Ethernet cables 1/2/3/6 and 4/5/7/8 provide power supply simultaneously. |
| | PoE port | Ports 1 to 4 |
| | Hi-PoE port | Port 1 |
| | Max. port power | Port 1: 60 W Ports 2 to 4: 30 W |
| | PoE power budget | 60 W |
| Dialing function | Long range | Ports 3 and 4: up to 300 m; and the speed rate of the port is 10 Mbps. |
| | Port isolation | Ports 1 to 4: port isolation mode to improve network security. |
| | PoE watchdog | Ports 1 to 4: auto detect and restart the cameras that do not respond. |
| General | Shell | Metal material, fan-free design |
| | Net Weight | 0.27 kg (0.59 lb) |
| | Dimension (L × H × D) | 121 mm × 88.1 mm × 27.6 mm (4.76" × 3.47" × 1.09") |
| | Operating temperature | -10 °C to 40 °C (14 °F to 104 °F) |
| | Storage temperature | -40 °C to 85 °C (-40 °F to 185 °F) |
| | Operating humidity | 5% to 95% (no condensation) |
| | Storage humidity | 5% to 95% (no condensation) |
| | Power supply | 48 VDC, 1.35 A |
| | Power consumption in idle | < 5W |
| | Max. power consumption | 65 W |
| Power source | 65 W | |
| Approval | EMC | FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010 +A1: 2015); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016) |
| | Safety | UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013) |
| | Chemistry | CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006) |

Physical Interface

Front panel:




Back panel:




Available Model

DS-3E0505HP-E

Dimension (unit: mm)



Typical Application



Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com