



Jantar

Entry control for home and office



Single door access controllers Rex O-3-A / K-3-A / X-3-A (13,56 MHz)



Rex O-3-A



Rex K-3-A



Rex X-3-A



- Single door compact access controllers with built-in proximity cards and tags readers with capacitive keypad or card holder
- In O/K/X A-type housing for surface installation
- Reading frequency 13,56MHz
- For advanced access control systems and home automation
- Designed for business and government buildings, hotels, R&D facilities, financial institutions, server rooms, archives, hospitals, shops, labs, etc.
- RS-485 and TCP/IP communication
- Internal memory for 1.000 cards and 10.000 events
- Door status and push buttons inputs, transistor door strike output
- Signalization of the door status by changing the colour of hand logo (red/green flashing - locked, green - unlocked, red - error) or by changing the color of the keypad (amber - locked, green - unlocked, red - error)

TECHNICAL DATA

- **Dimension: 90 x 90 x 17 mm (Reader O/K-3-A), 90 x 90 x 21 mm (Rex X-3-A)**
- **Reading frequency: 13,56 MHz**
- **Reading distance: up to 5 cm**
- **Internal memory for 1.000 cards and 10.000 events**
- **IP45**
- **External power supply 9 to 14 V DC (Spider W5-B, Spider W40, Spider W40-B, Spider H20, Spider H20-B)**
- **Anti-tamper alarm**
- **Operating temperature: from -20° to +40° C**
- **Max. current consumption: 0.2 A**
- **Color changing transparent part of the casing and buzzer for door status signalization**

ORDERING CODES

Code	Specification
Rex O-3-A	Single door access controller in O-A housing, 13,56 MHz
Rex K-3-A	Single door access controller with capacitive keypad in K-A housing, 13,56 MHz
Rex X-3-A	Single door access controller with card holder in X-A housing, 13,56 MHz