

Description

conventional (non-addressable) photoelectric smoke detectors are state-of-the-art detectors suitable for connection to conventional (non-addressable) fire detection control and indicating equipment, or to addressable fire detection control and indicating equipment that can accept conventional (non-addressable) type detectors.

Advanced electronics in conjunction with a photoelectric smoke sensing chamber provide early detection of smoke and high immunity against unwanted alarms.

The conventional (non-addressable) detectors provide fire detection and alarm system designers with an economical smoke detector for life safety and property protection applications.

Approvals

Detectors have CE approval

Features

- Advanced algorithms provide advanced detection discrimination
- Easy installation. No programming required
- Low maintenance
- Sleek low-profile housing design
- Stable photoelectric smoke sensing chamber. No adjustment or replacement required
- High immunity against unwanted alarms
- Surface-mount device (SMD) circuit board design
- Dual LEDs for 360° visibility
- 4-wire models for DC 12 V operation
- 4-wire models include a N/C or N/O alarm relay output
- 4-wire models available with auto-reset function only for DS-PDSMK-4BAR
- 4-wire models available with an internal sounder only for DS-PDSMK-4BAR



DS-PDSMK-4BAR



DS-PDSMK-4

Specifications

	DS-PDSMK-4	DS-PDSMK-4BAR
Operating voltage	DC (10.2 ~ 13.8) V	
Start-up current	≤ 200 μA	
Start-up time	≤ 60 s	
Standby current	≤ 60 μA	
Alarm current (max)	35 mA	
Maximum permitted current	80 mA	
Sampling time	8 s	
Reset voltage	≤ 1 V	
Reset time	≤ 1 s	
Alarm response threshold (smoke)	(0.10 ~ 0.16) dB/m (1.51 ~ 2.73) % / ft obscuration	
Alarm relay	SPST. N/O or N/C. 1.0 A @ DC 30 V / 0.5 A @ AC 125V	
Auto reset time	—	28 s ~ 35 s
Sounder output	—	≥ 85 dB @ 3 m
Operating temperature	0 °C ~ +50 °C	
Operating humidity	0 % ~ 95 % RH, non-condensing	
Storage temperature	-25 °C ~ +80 °C	
Storage humidity	0 % ~ 98 % RH, non-condensing	
Alarm indicator	Two continuous emitting red LEDs	
Dimensions (excluding contacts)	Φ 100 mm × 35 mm	
Ingress protection rating	IP-42	

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com