

TESTER4-IP-3HD

SAFIRE Universal CCTV tester
IP | HDTV | HDCVI | AHD | CVBS
Touch screen 4.3"
IP, HD and analogue video
ONVIF and Dahua and Hikvision
Android App
Digital multimeter



SAFIRE Universal CCTV tester for IP, HDTV, HDCVI, AHD and Analogue CVBS cameras.

Complete tool for professional installation and maintenance of CCTV systems for both analogue systems and IP devices. Integrates a capacitive touch screen of 4.3" and resolution of 800x480 pixels. Wide OSD menu that allows you to configure various functions easily and intuitively:

Video display: IP / HDTV / HDCVI / AHD / Analogue CVBS
HDMI output for use in monitor
IP cameras: Connection via RJ45 and WiFi, supports 1080p
Supports ONVIF and incorporates Android applications from manufacturers such as Dahua and Hikvision
Scanning of IP addresses and PING Test, FTP server and DHCP
Recording/Playback of video and image captures on Micro SD card (4GB included)
Scanning, control and test of PTZ cameras by port RS485 and network
Audio test audio (input/output Jack and Network) and recording with storage
Power supply outputs: DC 12 V 2A / USB DC 5 V 2A / PoE DC 48 V 24W
Test for PoE power supply, link test and switch ports Locator
Test of coaxial and UTP cable
Coaxial and network cable identifier by audible signal
Digital multimeter
LED flashlight lighting

As accessories, it incorporates a BNC-BNC video cable, a cable for connection RS485, audio probe, probe for multimeter, power adapter cable and a cable test. Easy to operate and portable thanks to its lithium battery with autonomy for 16 hours, as well as permanently connected to the mains.

Specifications

Brand	SAFIRE
Screen	Capacitive touch 4.3" (resolution 800x480)
Formats	IP / HDTV / HDCVI / AHD / Analogue CVBS
Video settings	Brightness, contrast and saturation
Inputs	BNC (Formats), RS232, RS485, RJ45 (LAN/PSE/SCAN), USB, Audio
Outputs	BNC, HDMI, DC12V2A, DC5V2A, PoE (24W max.)
PTZ	RS485 and network
Speaker	Incorporated
Digital multimeter	Voltage, current, resistance and capacitance
Video generator	Multicolour bar
Cable Tester	Independent accessory
Storage	Micro SD up to 32 GB (4 GB included)
Power	Lithium Battery 7.4 V 5000 mAh
Charger	DC12 V 2.0 A
Temp. operation	-10° C ~ +50° C
Dimensions / Weight	213 mm x 137 mm x 55 mm / 830 g