

IndoorCam

Tech specs

Where to buy

Tech specs

IndoorCam

Indoor Wi-Fi security camera with PIR motion detector and built-in AI



Device compatibility

Check

Video stream

Camera

4 MP CMOS sensor

Resolution

up to 2688 × 1520 px

Camera viewing angles

horizontal: 110°

vertical: 60°

Video protocol

JetSparrow

Fast and encrypted peer-to-peer video protocol developed by Ajax Systems.

Storage options

Ajax Cloud (coming soon)

NVR

Video codec

H.264

Dynamic range

HDR

Improves the accuracy of detail in bright and dark scenes.

Communication channel

Wi-Fi

802.11 b/g/n module

2.4 GHz, up to 2 Mbit/s for the channel 2K video.

Jeweller and Wings communication technologies

Proprietary wireless communication technologies to transmit commands, alarms, events, and photo verifications. They serve as a backup communication channel when the device is added to the hub.

Learn more >

Key features

Two-way communication

Clear and loud voice communication between users and the device.

Motion detection

The device detects movement using a built-in PIR sensor and software image frame analysis.

Object detection

using AI

- People.
- Pets.
- Vehicles.

Smart IR illumination

up to 8 m

Automatic adjustment of intensity in real time to avoid overexposure. This allows you to see objects that are far away or too close to the camera in low-light conditions.

Visual verification of Ajax alarms

The system allows you to set up a scenario when Ajax detectors activate selected cameras to start recording. The result is immediately sent to the mobile or desktop monitoring app.

Microphone

For two-way communication and sound recording at the site.

Speaker volume

TBC

Audio codec

G722

Audio processing

Always active noise suppression and echo cancellation.

LED indication

An LED indicator shows the actual state of the device.

PIR detection

Sensitive elements

1 × PIR sensor

Motion detection distance

up to 4 m

Depends on the sensitivity level adjusted in the device settings.

Motion detection angle

horizontal: 110°

vertical: 60°

Sensitivity

3 levels

Adjusted by a PRO or a user with admin rights in Ajax apps.

Installation recommendations

The device is designed for indoor use only.

It is **not recommended** to install the device in direct sunlight. This may cause overheating and damage to the device's electrical components.

Sabotage protection

Holding screw

secures the device on the mounting bracket

mTLS

Encrypted connection for data protection.

Authentication

via Ajax Cloud

Without local access rights.

Secure Boot

Protection against firmware spoofing.

OTA signature verification

Secure automatic firmware update.



Privacy

Access rights distribution for users in mobile apps and for monitoring operators in PRO Desktop.

Communication loss detection

Wi-Fi: can be set from 30 s

Jeweller/Wings: after 36 s

Detection time depends on Ajax Cloud connection and Jeweller or Jeweller/Fibra settings.

Power supply

Power supply unit

12 V \pm 20%, 1 A

Device power consumption

TBC



Enclosure

Dimensions

128 × 74 × 76 mm

Weight

235 g

Operating temperature range

from 0 °C to +40 °C

Operating humidity

up to 90% with no condensation

Protection class

IP20



Color

Black

White

RAL 9005



RAL 9003



Complete set

IndoorCam

Power supply unit

Installation kit

Quick start guide

Additional information

Compliance with standards

User manual

[Learn more >](#)

[Learn more >](#)

Warranty

24 months

[Learn more >](#)

Products

- Intrusion protection
- Video surveillance
- Fire and life safety
- Comfort and automation
- All products
- Services
- System integrations

Solutions

- Customer stories
- Solutions by facility type
- Upgrades and retrofits
- Why Ajax
- How it works

Support

Company

- Blog
- About us
- Press page
- Events
- Career
- Reviews and feedback

Subscribe

Subscribe to our emails about secure life. No spam.

[Subscribe](#)

Request extra help

 support@ajax.systems

[Ajax Ready products](#)

Software

[For users](#)



[Ajax PRO: Tool for Engineers](#)

[Ajax Desktop](#)

[Ajax PRO Desktop](#)

[Ajax Translator](#)

[Scenarios](#)



[Manuals and articles](#)

[Compliance with standards](#)

Tools

[Ajax device compatibility](#)

[Video storage calculator](#)

[Video device calculator](#)

[Battery life calculator](#)

[Radio communication range calculator](#)

[Switches and outlets configurator](#)

[Fibra power supply calculator](#)

[All web tools](#)

[IndoorCam | Technical specifications](#)

For partners

[For partners](#)

[Ajax Academy](#)

[Partner Portal](#)

[@AjaxSystemsSupport_Bot](#)



4,000,000 people worldwide under Ajax protection

[Report mistake](#)

[Suggest a feature](#)

