

NVR

More 

Tech specs

NVR (16-ch)

Network video recorder for 16 channels



Videostream

NVR models

16-channel

With up to 4K resolution (25/30 FPS).

IP cameras

- ONVIF (Profile S/T)
- RTSP

[Learn more](#) >

Storage

hard drive with a capacity of up to 16 TB (SATA connectivity, 3.5" size)

HDD not included. The hard drive with power consumption of up to 7 W can be connected.

Decoding formats

H.265

H.264

Bandwidth

up to 100 Mbps

Recommendations

The device operating voltage is 110–240 V~.

NVR is designed for indoor installation only.

Communication channels

Ethernet

up to 100 Mbps

Bluetooth

BLE frequency band: 2.400–2.4835 GHz

To set up an Ethernet connection.

Radio signal power

2.5 mW (100 mW limit)

Key features

Motion detection

NVR has built-in software to detect the motion in the frame. Possible to switch between image analysis by NVR or camera algorithms.

In-app video management system

- Videowall that combines images from all connected cameras.
- Event filters.
- Timeline with smooth preview.

Visual verification of Ajax alarms

NVR allows setting up a scenario in which Ajax detectors trigger specific cameras to start recording. This results straight in mobile and desktop (monitoring) apps.

Support for ONVIF authorization

Profile S

Profile T (partially)

Ajax cameras and NVRs can be integrated into third-party video management systems (VMS).

[Learn more](#) >

Privacy

Access rights distribution for users in mobile apps and for monitoring operators in PRO Desktop.

Power supply

Main

110–240 V~, 50/60 Hz, 0.6 A

Up to 24 W of mains power consumption.

Backup

CR2032 battery, 3 V

Only to power the system clock.

Sabotage protection

Tamper alarm

Notifications about attempts to detach the device from the surface or remove it from the mounting panel.

[Learn more](#) >

Enclosure

Dimensions

193 × 193 × 47 mm



Weight

615 g

Without a hard drive.

Operating temperature range

from 0 °C to +40 °C



47 mm

Operating humidity

up to 75%

Protection class

IP20

Colors

Black



White



Complete set

NVR

SmartBracket mounting panel

[Power cable](#)[Ethernet cable](#)[Installation kit](#)[Quick start guide](#)

Certification and compliance with standards



NVR (16-ch)



Additional information

Compliance with standards

[Learn more](#) >

User manual

[Learn more](#) >

Warranty

24 months

[Learn more](#) >[Subscribe](#)

Subscribe to our emails about secure life. No spam.

[Subscribe](#)

Request extra help

- [!\[\]\(48a7667d09d5a06397e047ee4537bb6f_img.jpg\) support@ajax.systems](mailto:support@ajax.systems)
- [!\[\]\(3df135a685d1b545c4fa64a5f3516545_img.jpg\) @AjaxSystemsSupport_Bot](https://www.telegram.org/)
- [!\[\]\(de62294faded52808857591d246c2e7a_img.jpg\) Send a request](https://www.ajax.systems/contact)

**4,000,000**

people worldwide under Ajax protection

Rating 4.7

Suggest a feature




Products

- Intrusion protection
- Video surveillance
- Fire and life safety
- Comfort and automation
- All products
- Services
- System integrations
- Ajax Ready products

Software

- For users
- Ajax PRO: Tool for Engineers
- Ajax Desktop
- Ajax PRO Desktop
- Ajax Translator
- Scenarios



Solutions

- Customer stories
- Solutions by facility type
- Upgrades and retrofits
- Why Ajax
- How it works

Support

- Manuals and articles
- Compliance with standards

Tools

- Ajax device compatibility
- Video storage calculator

[Video device calculator](#)[Battery life calculator](#)[Radio communication range calculator](#)[Switches and outlets configurator](#)[Fibra power supply calculator](#)[All web tools](#)

Company

[Blog](#)
[About us](#)
[Press page](#)
[Events](#)
[Career](#)
[Reviews and feedback](#)

For partners

[For partners](#)
[Ajax Academy](#)
[Partner Portal](#)

 [Hrvatska](#) [Privacy policy](#) [Report a vulnerability](#) [GDPR White Paper](#) [NDAA Statement](#) [Cookie policy](#)
[Anti-Spam Policy](#) [End user agreement](#) [Warranty](#)

© 2025 AJAX SYSTEMS CH. All rights reserved